



Hohlstahl

Rostfrei und säurebeständig, gegläht und gebeizt.

Toleranzen: ISO 2938-1974

Werksabnahmezeugnis: EN 10204/3.1

● Lager

Hohlstahl
Rostfrei und säurebeständig,
geglüht und gebeizt

Toleranzen: ISO 2938-1974
Werksabnahmezeugnis: EN 10204/3.1

Abmessung mm	Kg/m	EN	1.4301	1.4571
32 x 16	5,100		●	●
x 20	4,100		●	●
36 x 16	6,700		●	●
x 20	5,800		●	●
x 25	4,500		●	●
40 x 20	7,700		●	●
x 25	6,400		●	●
x 28	5,400		●	●
45 x 20	10,400		●	●
x 28	8,100		●	●
x 32	6,700		●	●
50 x 25	12,100		●	●
x 32	9,700		●	●
x 36	8,100		●	●
56 x 28	15,100		●	●
x 36	12,100		●	●
x 40	10,300		●	●
63 x 32	19,000		●	●
x 36	17,300		●	●
x 40	15,500		●	●
x 45	12,000		●	●
x 50	10,100		●	●
71 x 36	24,100		●	●
x 40	22,300		●	●
x 45	19,800		●	●
x 56	13,100		●	●
75 x 40	26,000		●	●
80 x 40	31,000		●	●
x 45	28,500		●	●
x 50	25,600		●	●
x 63	16,900		●	●
85 x 45	33,700		●	●
90 x 50	36,400		●	●
x 56	32,600		●	●
x 63	27,700		●	●
x 71	21,300		●	●
95 x 50	42,200		●	●
100 x 56	44,600		●	●
x 63	39,700		●	●
x 71	33,300		●	●
x 80	25,200		●	●
106 x 56	52,400		●	●
x 63	47,500		●	●

Hohlstahl
Rostfrei und säurebeständig,
geglüht und gebeizt

Toleranzen: ISO 2938-1974
Werksabnahmezeugnis: EN 10204/3.1

Abmessung mm	Kg/m	EN	1.4301	1.4571
106 x 71	41,000		●	●
x 80	32,900		●	●
112 x 63	55,600		●	●
x 71	49,200		●	●
x 80	41,100		●	●
x 90	30,800		●	●
118 x 63	64,200		●	●
x 71	57,800		●	●
x 80	49,700		●	●
x 90	39,500		●	●
125 x 71	68,400		●	●
x 80	60,300		●	●
x 90	50,100		●	●
x 100	38,800		●	●
132 x 71	79,600		●	●
x 80	71,500		●	●
x 90	61,300		●	●
x 106	42,500		●	●
140 x 80	85,000		●	●
x 90	74,800		●	●
x 100	63,500		●	●
x 112	48,100		●	●
150 x 80	104,000		●	●
x 95	88,200		●	●
x 106	75,000		●	●
x 125	48,900		●	●
160 x 112	86,400		●	●
x 122	72,600		●	●
x 132	57,500		●	●
170 x 106	110,930		●	●
x 118	99,000		●	●
x 130	81,100		●	●
x 140	64,900		●	●
180 x 125	110,700		●	●
x 150	69,100		●	●
190 x 132	122,900		●	●
x 150	92,100		●	●
x 160	73,300		●	●
200 x 140	127,700		●	●
x 160	90,200		●	●
212 x 130	175,600		●	●
x 150	140,950		●	●
x 170	100,500		●	●

Hohlstahl
Rostfrei und säurebeständig,
geglüht und gebeizt

Toleranzen: ISO 2938-1974
Werksabnahmezeugnis: EN 10204/3.1

Abmessung mm	Kg/m	EN	1.4301	1.4571
224 x 140	191,400		●	●
x 180	111,300		●	●
236 x 150	207,800		●	●
x 190	122,700		●	●
250 x 200	140,900		●	●