



# Stabstahl

- Lager

Rundstahl  
Warmgewalzt bzw. geschmiedet,  
gebeizt oder überdreht

Toleranzen: EN 10060/DIN 7527  
Werksabnahmezeugnis: EN 10204/3.1

Abmessung mm	Kg/m	EN 1.4021	1.4057	1.4301	1.4305	1.4404	1.4462	1.4571
20,00	2,470			●				●
25,00	3,853		●	●				●
30,00	5,550	●	●	●		●	●	●
35,00	7,550	●	●	●		●	●	●
40,00	9,860	●	●	●	●	●	●	●
45,00	12,500	●	●	●	●	●	●	●
50,00	15,400	●	●	●	●	●	●	●
55,00	18,700	●	●	●	●	●	●	●
60,00	22,200	●	●	●	●	●	●	●
65,00	26,000	●	●	●	●	●	●	●
70,00	30,210	●	●	●	●	●	●	●
75,00	34,700	●	●	●	●	●	●	●
80,00	39,460	●	●	●	●	●	●	●
85,00	44,560	●		●	●	●	●	●
90,00	49,940	●	●	●	●	●	●	●
95,00	55,640	●	●	●	●	●	●	●
100,00	61,550	●	●	●	●	●	●	●
105,00	67,970	●		●	●	●		●
110,00	74,600	●	●	●	●	●	●	●
115,00	81,540	●		●	●	●		●
120,00	88,780	●	●	●	●	●	●	●
125,00	96,330	●		●	●	●		●
130,00	104,200	●	●	●	●	●	●	●
135,00	112,360			●	●			
140,00	121,000	●	●	●	●	●	●	●
145,00	129,630			●		●		●
150,00	139,000	●	●	●	●	●	●	●
155,00	148,100	●				●		●
160,00	158,000	●	●	●	●	●	●	●
165,00	168,000					●		●
170,00	178,000	●	●	●	●	●	●	●
180,00	200,000	●	●	●	●	●	●	●
190,00	223,000		●	●	●	●		●
200,00	247,000	●	●	●	●	●	●	●
210,00	272,000	●	●	●	●	●		●
220,00	298,000	●	●	●	●	●	●	●
230,00	326,100		●	●	●	●		●
240,00	355,100	●	●	●		●		●
250,00	386,000	●	●	●	●	●	●	●
260,00	416,800	●		●	●			●
270,00	452,000			●				●
280,00	483,400			●	●	●		●
300,00	555,000		●	●	●	●	●	●

Rundstahl  
 Warmgewalzt bzw. geschmiedet,  
 gebeizt oder überdreht

Toleranzen: EN 10060/DIN 7527  
 Werksabnahmezeugnis: EN 10204/3.1

Abmessung mm	Kg/m	EN 1.4021	1.4057	1.4301	1.4305	1.4404	1.4462	1.4571
310,00	592,000			●		●		●
320,00	634,880			●		●		●
325,00	651,200			●				
330,00	671,000			●		●		●
340,00	712,000			●		●		●
350,00	755,300			●		●	●	●
360,00	799,300			●		●		●
380,00	890,000			●		●		●
400,00	986,500			●		●	●	●
425,00	1114,000			●		●		●
450,00	1248,000			●		●		●
475,00	1391,000			●		●		●
500,00	1541,000			●		●		●
525,00	1699,000			●		●		●

Rundstahl  
Blankgezogen oder poliert

Toleranzen: EN 10278  
Länge: 3-3,2 m  
Werksabnahmezeugnis: EN 10204/3.1

Abmessung mm	Kg/m	EN 1.4021	1.4057	1.4104	1.4301	1.4305	1.4404	1.4571
3,00	0,060				●			
4,00	0,099				●	●	●	●
5,00	0,154				●	●	●	●
6,00	0,222			●	●	●	●	●
7,00	0,302				●	●		
8,00	0,395			●	●	●	●	●
9,00	0,499				●			
10,00	0,617	●	●	●	●	●	●	●
12,00	0,888	●	●	●	●	●	●	●
13,00	1,042			●	●			
14,00	1,208	●	●	●	●	●		●
15,00	1,387	●	●	●	●	●	●	●
16,00	1,578	●	●		●	●		●
17,00	1,782				●	●		
18,00	1,998	●	●	●	●	●		●
19,00	2,226				●	●		
20,00	2,470	●	●	●	●	●	●	●
22,00	2,984	●	●	●	●	●		●
24,00	3,551				●	●		
25,00	3,854	●	●		●	●	●	●
26,00	9,168	●	●		●	●		●
28,00	4,836	●	●		●	●		●
30,00	5,549	●	●		●	●	●	●
32,00	6,313	●	●	●	●	●		●
34,00	7,130				●			
35,00	7,553	●	●		●	●	●	●
36,00	7,994	●	●	●	●	●		●
38,00	8,905	●	●		●	●		●
40,00	9,871	●	●	●	●	●	●	●
42,00	10,881	●	●		●	●		
45,00	12,500	●	●		●	●	●	●
50,00	15,432	●	●		●	●	●	●
55,00	18,657				●	●		●
60,00	22,222				●	●		●
65,00	26,110				●	●		●
70,00	30,211			●	●	●		●
75,00	34,722				●	●		
80,00	39,526				●	●		●
90,00	50,000				●	●		
100,00	61,728				●	●		●

Rundstahl  
Geschliffen K240  
Länge 6 m

Abmessung mm	Kg/m	EN 1.4301
8,00	0,395	●
10,00	0,617	●
12,00	0,888	●

Rundstahl  
Blankgezogen oder poliert

*Toleranz: EN 10278*  
*Länge: 6 m*  
*Werksabnahmezeugnis: EN 10204/3.1*

Abmessung mm	Kg/m	EN 1.4301
8,00	0,395	●
10,00	0,617	●
12,00	0,888	●
14,00	1,208	●
15,00	1,387	●
18,00	1,998	●
20,00	2,470	●

U-Profil  
Lasergeschweißt oder  
gewalzt, gebeizt

Toleranz: EN 10279  
Länge: 6-6,2 m  
Werksabnahmezeugnis: EN 10204/3.1

Abmessung mm	Kg/m	EN 1.4301
20 x 10 x 3,0 x 3,5	0,860	●
30 x 15 x 4,0 x 4,5	1,740	●
40 x 20 x 4,0 x 4,5	2,300	●
50 x 25 x 5,0 x 6,0	3,860	●
50 x 38 x 5,0 x 7,0	5,600	●
60 x 30 x 6,0 x 6,0	5,100	●
65 x 42 x 5,0 x 7,5	7,100	●
80 x 45 x 6,0 x 8,0	8,650	●
100 x 50 x 6,0 x 8,5	10,600	●
120 x 55 x 7,0 x 9,0	13,400	●

T-Profil  
Lasergeschweißt oder  
gewalzt, gebeizt

Toleranz: EN 10055  
Länge: 6-6,2 m  
Werksabnahmezeugnis: EN 10204/3.1

Abmessung mm	Kg/m	EN 1.4301
25 x 25 x 3,5	1,260	●
30 x 30 x 3,0	1,350	●
30 x 30 x 4,0	1,770	●
35 x 35 x 4,0	2,090	●
40 x 40 x 4,0	2,400	●
40 x 40 x 5,0	2,960	●
50 x 50 x 5,0	3,751	●
50 x 50 x 6,0	4,511	●
60 x 60 x 6,0	5,402	●
70 x 70 x 7,0	7,305	●
80 x 80 x 8,0	9,506	●
90 x 90 x 9,0	12,195	●
100 x 100 x 10	15,106	●
120 x 120 x 13	23,202	●

**TB-Profil**  
Lasergeschweißt, gebeizt

*Toleranz: EN 10055*  
*Länge: 6-6,2 m*  
*Werksabnahmezeugnis: EN 10204/3.1*

Abmessung mm	Kg/m	EN 1.4301
60 x 30 x 5,5	3,701	●
70 x 35 x 6,0	4,660	●
80 x 40 x 7,0	6,203	●
100 x 50 x 8,5	9,001	●

**HEB-Profil**  
Lasergeschweißt, gebeizt

*Toleranz: DIN 1025-2*  
*Länge: 6-6,2 m*  
*Werksabnahmezeugnis: EN 10204/3.1*

Abmessung mm	Kg/m	EN 1.4301
100 x 100 x 6,0 x 10,0	20,408	●
120 x 120 x 6,5 x 11,0	28,571	●

**IPE-Profil**  
Lasergeschweißt, gebeizt

*Toleranz: DIN 1025-5*  
*Länge: 6-6,2 m*  
*Werksabnahmezeugnis: EN 10204/3.1*

Abmessung mm	Kg/m	EN 1.4301
80 x 46 x 3,8 x 5,2	6,203	●
100 x 55 x 4,1 x 5,7	8,299	●
120 x 65 x 4,4 x 6,3	10,695	●
140 x 73 x 4,7 x 6,9	13,193	●

Winkelstahl  
Gewalzt, gegläht und gebeizt  
Gleichschenkelig

Toleranz: EN 10056-1  
Länge: ca. 6.000 mm  
Werksabnahmezeugnis: EN 10204/3.1

Abmessung mm	Kg/m	EN 1.4301	1.4571	1.4301
			allseitig geschliffen K 240	
20 x 20 x 3,0	0,910	●	●	
20 x 20 x 4,0	1,140	●		
25 x 25 x 3,0	1,150	●	●	
25 x 25 x 4,0	1,480	●	●	
30 x 30 x 3,0	1,390	●	●	●
30 x 30 x 4,0	1,800	●	●	
35 x 35 x 4,0	2,100	●	●	
40 x 40 x 4,0	2,450	●	●	●
40 x 40 x 5,0	3,030	●	●	
50 x 50 x 5,0	3,870	●	●	●
50 x 50 x 6,0	4,550	●	●	
60 x 60 x 6,0	5,530	●	●	
70 x 70 x 7,0	7,540	●	●	
80 x 80 x 8,0	9,800	●	●	
100 x 100 x 10,0	15,300	●	●	

Ungleichschenkelig

Abmessung mm	Kg/m	EN 1.4301
30 x 20 x 3	1,150	●
30 x 20 x 4	1,500	●
40 x 20 x 4	1,800	●
45 x 30 x 5	2,750	●
50 x 30 x 5	3,020	●
60 x 30 x 5	3,410	●
60 x 40 x 5	3,750	●
60 x 40 x 6	4,450	●
80 x 40 x 6	5,500	●
80 x 40 x 8	7,140	●
100 x 50 x 6	6,900	●
100 x 50 x 8	9,080	●

Vierkantstahl  
Blankgezogen

Toleranz: EN 10278

Länge: 3-3,2 m

Werksabnahmezeugnis: EN 10204/3.1

Abmessung mm	Kg/m	EN 1.4301	1.4305
6,00	0,283	●	
8,00	0,500	●	
10,00	0,790	●	●
12,00	1,130	●	●
14,00	1,539	●	
15,00	1,766	●	●
16,00	2,010	●	
20,00	3,141	●	●
25,00	4,907	●	●
30,00	7,067	●	●
40,00	12,563	●	●
50,00	19,646	●	●
60,00	28,260		●

Vierkantstahl  
Gewalzt, abgeschreckt und gebeizt

Toleranz: EN 10059  
Länge: 4-6 m  
Werksabnahmezeugnis: EN 10204/3.1

Abmessung mm	Kg/m	EN 1.4301	1.4571
20,00	3,141	●	●
25,00	4,907	●	●
30,00	7,067	●	●
35,00	9,620	●	
40,00	12,563	●	●
50,00	19,646	●	●
60,00	28,280	●	●
80,00	50,240	●	
100,00	78,740	●	

Sechskantstahl  
Blankgezogen

Toleranz: EN 10278

Länge: 3-3,2 m

Werksabnahmezeugnis: EN 10204/3.1

Abmessung mm	Kg/m	EN 1.4301	1.4305	1.4571
10,00	0,680	●	●	
13,00	1,140	●	●	
17,00	1,965	●	●	●
19,00	2,455	●	●	●
22,00	3,291	●	●	●
24,00	3,917	●	●	●
27,00	4,958	●	●	●
30,00	6,120	●	●	●
32,00	6,964	●	●	●
36,00	8,818	●	●	●
41,00	11,442	●	●	●

Flachstahl  
Warmgewalzt, gegläht und gebeizt

Toleranz: EN 10058  
Länge: 4-6 m  
Werksabnahmezeugnis: EN 10204/3.1

Abmessung mm	Kg/m	EN 1.4301	1.4571
15 x 8	0,940	●	
x 10	1,410	●	
20 x 5	0,810		●
x 6	0,960	●	
x 8	1,290	●	
x 10	1,610	●	
x 12	1,930	●	
x 15	2,360	●	
25 x 8	1,610	●	
x 10	2,020	●	●
x 12	2,420	●	●
x 15	3,000	●	
30 x 4	0,970	●	
x 5	1,210	●	●
x 8	1,930	●	
x 10	2,420	●	●
x 12	2,900	●	
x 15	3,560	●	●
x 20	4,840	●	●
35 x 8	2,260	●	
x 10	2,820	●	
x 12	3,390	●	
x 15	4,150	●	
40 x 5	1,610	●	
x 6	1,930	●	
x 8	2,580	●	●
x 10	3,220	●	●
x 12	3,870	●	●
x 15	4,470	●	●
x 20	6,450	●	●
x 25	7,850	●	
x 30	9,420	●	●
45 x 5	1,810	●	
x 15	5,300	●	
50 x 5	2,020	●	
x 6	2,420	●	
x 8	3,220	●	●
x 10	4,030	●	●
x 12	4,840	●	●
x 15	5,930	●	●
x 20	8,060	●	●
x 25	10,100	●	●
x 30	11,780	●	●

Flachstahl  
Warmgewalzt, geblüht und gebeizt

Toleranz: EN 10058  
Länge: 4-6 m  
Werksabnahmezeugnis: EN 10204/3.1

Abmessung mm	Kg/m	EN 1.4301	1.4571
60 x 5	2,420	●	
x 6	2,900	●	
x 8	3,870	●	●
x 10	4,840	●	●
x 12	5,800	●	●
x 15	7,110	●	●
x 20	9,670	●	●
x 25	12,100	●	
x 30	14,100	●	●
x 40	18,840	●	
70 x 8	4,510	●	
x 10	5,640	●	●
x 12	6,770	●	
x 15	8,240	●	●
x 20	11,300	●	●
80 x 8	5,160	●	●
x 10	6,450	●	●
x 12	7,740	●	●
x 15	9,400	●	●
x 20	12,900	●	●
x 25	16,100	●	●
x 30	18,800	●	●
x 40	25,120	●	
90 x 10	7,250	●	
100 x 5	3,931	●	
x 8	6,450	●	●
x 10	8,060	●	●
x 12	9,670	●	●
x 15	11,800	●	●
x 20	16,100	●	●
x 25	20,200	●	
x 30	23,600	●	●
x 40	31,400	●	●
120 x 10	9,420	●	
x 12	11,300	●	●
x 15	14,400	●	●
x 20	18,840	●	
x 25	23,550	●	
x 30	28,260	●	
150 x 12	14,130	●	
x 15	18,000	●	
x 20	23,550	●	
x 25	29,440	●	
x 30	35,330	●	

● Lager

Flachstahl  
Aus Blech geschnitten

Toleranz: ähnlich EN 10058  
Länge: 4 m  
Werksabnahmezeugnis: EN 10204/3.1

Abmessung mm	Kg/m	EN 1.4301	1.4571
10 x 3	0,236	●	
15 x 3	0,360	●	
x 4	0,480	●	
x 5	0,600	●	
x 6	0,750	●	
20 x 3	0,480	●	
x 4	0,650	●	
x 5	0,810	●	●
x 6	0,960	●	
x 8	1,290	●	
25 x3	0,600	●	
x 4	0,810	●	●
x 5	1,010	●	●
x 6	1,210	●	●
x 8	1,610	●	
x 10	2,020	●	
30 x 3	0,730	●	●
x 4	0,970	●	●
x 5	1,210	●	●
x 6	1,450	●	●
x 8	1,880	●	●
x 10	2,420	●	
35 x 5	2,260	●	
x 6	1,690	●	
40 x 3	0,970	●	●
x 4	1,290	●	●
x 5	1,610	●	●
x 6	1,930	●	●
x 8	2,580	●	●
x 10	3,220	●	●
x 12	3,870	●	
50 x 3	1,180	●	
x 4	1,610	●	●
x 5	2,020	●	●
x 6	2,420	●	●
x 8	3,220	●	●
x 10	4,030	●	●
x 12	4,840	●	
60 x 4	1,880	●	●
x 5	2,420	●	●
x 6	2,900	●	●
x 8	3,870	●	●
x 10	4,840	●	●

Flachstahl  
Aus Blech geschnitten

Toleranz: ähnlich EN 10058

Länge: 4 m

Werksabnahmezeugnis: EN 10204/3.1

Abmessung mm	Kg/m	EN 1.4301	1.4571
60 x 12	5,800	●	
70 x 5	2,750	●	
x 8	4,510	●	
x 10	5,640	●	●
80 x 5	3,140	●	●
x 6	3,870	●	●
x 8	5,160	●	●
x 10	6,450	●	●
x 12	7,740	●	
90 x 10	7,250	●	
100 x 5	3,930	●	●
x 6	4,840	●	●
x 8	6,450	●	●
x 10	8,060	●	●
x 12	9,670	●	
120 x 5	4,710	●	
x 6	5,650	●	
x 8	7,540	●	●
x 10	9,420	●	
150 x 6	7,070	●	
x 8	9,420	●	
x 10	11,780	●	
160 x 10	12,560	●	
200 x 8	12,563	●	
x 10	15,700	●	

Flachstahl  
Allseitig geschliffen K240

Toleranz: ähnlich EN 10058  
Länge: 4 m  
Werksabnahmezeugnis: EN 10204/3.1

Abmessung mm	Kg/m	EN 1.4301
20 x 4	0,650	●
x 5	0,810	●
x 6	0,960	●
x 8	1,290	●
25 x 4	0,810	●
x 5	1,010	●
x 6	1,210	●
30 x 4	0,970	●
x 5	1,210	●
x 6	1,450	●
x 8	1,930	●
x 10	2,420	●
35 x 4	1,130	●
x 5	1,410	●
x 6	1,690	●
40 x 4	1,290	●
x 5	1,610	●
x 6	1,930	●
x 8	2,580	●
x 10	3,220	●
50 x 5	2,020	●
x 6	2,420	●
x 8	3,220	●
x 10	4,030	●
60 x 5	2,420	●
x 6	2,900	●
x 8	3,870	●
x 10	4,840	●
80 x 4	2,510	●
x 5	3,140	●
x 6	3,870	●
x 8	5,160	●
x 10	6,450	●
100 x 6	4,840	●
x 8	6,450	●
x 10	8,060	●

Flachstahl  
Blankgezogen

Toleranz: EN 10278  
Länge: 3-4 m  
Werksabnahmezeugnis: EN 10204/3.1

Abmessung mm	Kg/m	EN 1.4301
10 x 3	0,236	●
x 4	0,314	●
x 5	0,393	●
12 x 4	0,377	●
x 5	4,710	●
x 6	0,565	●
15 x 5	0,589	●
x 8	0,943	●
x 10	1,177	●
20 x 3	0,471	●
x 4	0,628	●
x 5	0,786	●
x 6	0,943	●
x 8	1,261	●
x 10	1,572	●
x 12	1,883	●
x 15	2,364	●
25 x 4	0,786	●
x 5	0,981	●
x 6	1,181	●
x 8	1,572	●
x 10	1,961	●
x 12	2,364	●
x 15	2,941	●
x 20	3,929	●
30 x 4	0,941	●
x 5	1,181	●
x 6	1,410	●
x 8	1,880	●
x 10	2,360	●
x 12	2,830	●
x 15	3,530	●
x 20	4,710	●
35 x 8	2,200	●
x 20	5,501	●
40 x 4	1,260	●
x 5	1,570	●
x 6	1,880	●
x 8	2,510	●
x 10	3,140	●
x 12	3,774	●
x 15	4,717	●
x 20	6,289	●
x 25	7,874	●

● Lager

Flachstahl  
Blankgezogen

Toleranz: EN 10278  
Länge: 3-4 m  
Werksabnahmezeugnis: EN 10204/3.1

Abmessung mm	Kg/m	EN 1.4301
50 x 5	1,961	●
x 6	2,358	●
x 8	3,140	●
x 10	3,937	●
x 12	4,717	●
x 15	5,882	●
x 20	7,874	●
60 x 5	2,360	●
x 6	2,830	●
x 8	3,770	●
x 10	4,710	●
x 12	5,650	●
x 15	7,070	●
x 20	9,420	●
x 30	14,130	●
80 x 5	3,140	●
x 8	5,020	●
x 10	6,280	●
x 12	7,451	●
x 15	9,420	●
x 20	10,560	●
x 30	18,840	●
100 x 10	7,850	●
x 12	9,420	●
x 15	11,770	●
x 20	15,72	●